

T0293 CWDM Series

1270nm to 1450nm DFB TO-Can Package for 10Gb/s Applications



Product Brief



Description

The T0293 CWDM is a hermetically sealed device with a photo diode for optical output monitoring. It incorporates 1270nm to 1450nm single mode edge-emitting laser diode chips for use in uncooled applications up to 10.7Gb/sec. The laser is mounted into a TO header and is hermetically sealed with a specific lens cap. The laser design is buried hetero structure with multi-quantum well (MQW) active layers and distributed-feedback (DFB) grating layer. All laser chips come from wafers that have been certified using a representative lot of devices that must achieve an acceptable yield for burn-in and other multi-temperature, CW and dynamic tests.

Features

- Low threshold current
- High bandwidth
- Qualified as per intent of Telcordia GR-468
- Operating temperature -40 °C to 85 °C

Applications

- Supports performance up to 10.7Gb/sec bit rate
- LR1 SONET/SDH OC192/STM-64
- 10Gb/s Gigabit Ethernet
- 10Gb/s Fiber Channel

For product information and a complete list of distributors, please go to our web site: www.avagotech.com

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies in the United States and other countries. CyOptics and the CyOptics logo are trademarks of CyOptics, Inc. in the United States and other countries. Data subject to change. Copyright © 2005-2013 CyOptics, Inc. All rights reserved. AV02-4195EN - June 17, 2013

